



* Subject to technical changes.

Specifications

Model	Plunger stroke (mm)	Jaw stroke (Dia.) (mm)	Chucking Dia. Max. (mm)	Chucking Dia. Min. (mm)	Max. D.B. pull kN (kgf)	Max. clamping force kN (kgf)	Max. speed min ⁻¹ (r.p.m.)	I kg · m ²	Weight (kg)	Matching cyl.	Max. pressure MPa (kgf/cm ²)
2M-05	15	10.9	135	14	6.5(660)	11(1120)	4500	0.02	6	RK-75(N)	1.8(18)
2M-06	20	14.5	165	14	14.3(1460)	24(2450)	4000	0.04	12.2	RK-100(N)	2.0(20)
2M-08	23	16.7	210	17	19.6(2000)	36.6(3730)	3500	0.13	23	RK-125(N)	1.9(19.3)
2M-10	27	19.6	254	22	26.1(2660)	49.3(5030)	3000	0.3	34.3	RK-150(N)	1.8(18.6)
2M-12	30	21.8	304	26	36(3670)	66(6730)	2500	0.71	59.1	RK-150(N)	2.4(24)

Dimensions

Model	A	B	C(H6)	D	E	G max.	G min.	H	J	K	L	L1	M	N	P	Q max.	Q min.	R max.	R min.	S	T
2M-05	135	55	80	100	7	6	-9	35	28	M12x1.75	4~M8	14	31	62	14	15.5	5	32.9	27.45	25	10
2M-06	165	74	140	104.8	5	101.6	81.6	36	34	M16x2	6~M10	14	37	73	20	17	8	38.7	31.4	31	12
2M-08	210	85	170	133.4	5	129	106	36	38	M20x2.5	6~M12	20	38	95	25	22.3	8.8	47.5	39.1	35	14
2M-10	254	89	220	171.4	5	160	133	36	45	M20x2.5	6~M16	18	43	110	30	32.3	12.8	53.9	44.1	40	16
2M-12	304	106	220	171.4	6	70	40	46	50	M24x3	6~M16	18	51	130	30	47.8	13.3	62.5	51.6	50	21